



Body Temperature Detection Systems



In-View Standard

Body Temp Detection System Package



Thermographic Bullet Body Temperature Camera, 160 X 120 Thermal, 4MP Optical, 6mm lens, temperature accuracy: $\pm 0.5^{\circ}\text{C}$, 24 VAC/12 VDC/PoE. Installation height: 1.5m. Optimal Face distance: 0.8m-2.5m



8-port 100Mbps Unmanaged PoE Switch plus 1 x network ports

In-View Enhanced

Body Temp Detection System Package



Thermographic Bullet Body Temperature Camera, 384 X 288 Thermal, 4MP Optical, 15mm lens, temperature accuracy: $\pm 0.5^{\circ}\text{C}$, 24 VAC/12 VDC/PoE. Installation height: 1.7m-2.5m. Face distance: 2m-7m. Blackbody Calibrator for thermographic devices, Temperature accuracy $\pm 0.3^{\circ}\text{C}$ Installation height: 1.7m



8-port 100Mbps Unmanaged PoE Switch plus 1 x network ports

Standard System Pricing

Enhanced System Pricing

Item	Purchase £	Rental £	Item	Purchase £	Rental £
1 x 3 or 6mm Camera	£3,130	£120 p/w	1 x 15mm Camera	£8,220	£350 p/w
1 x Adapter			1 x Adapter		
1 x Switch			1 x Blackbody calibrator		
1 x Cable			1 x Switch		
			1 x Cable		

Extras

Extras

Item	Purchase £	Rental £	Item	Purchase £	Rental £
Laptop	£596	n/a	Laptop	£596	n/a
Monitor	£180	n/a	Monitor	£180	n/a
Tripod	£240	£10p/w	Tripod	£240	£10p/w
NVR Recorder	£391	£25p/w	NVR Recorder	£391	£25p/w
Blackbody Calibrator	£1,210	£45p/w			
Installation	-----	£350 -----	Installation	-----	£350 -----
Decommission	-----	£175 -----	Decommission	-----	£175 -----

Specification Comparison & Prices

Temperature Screening Metal Detector Door Solution



All in one Metal detector door and thermal camera - no need to order the thermal camera separately; but if accuracy of $\pm 0.3^{\circ}\text{C}$ is needed, then blackbody calibrator is required to order separately.

LCD screen with real time temperature display and people counting statistics.

Light & sound alarm.

Accuracy: $\pm 0.5^{\circ}\text{C}$

Range: 30-45 $^{\circ}\text{C}$

Wall-Mounted / Stand-Mounted Touch-free Temperature Screening Terminal



Thermographic technology, temperature range: 30-45 $^{\circ}\text{C}$, accuracy: $\pm 0.5^{\circ}\text{C}$

Temperature screening of forehead

Authentication distance: 0.5m-1.5m, height: 1.2-1.9m

Temperature screening with visual results and audio prompt. LCD touch screen

Walk Through System Pricing

Item	Purchase £	Rental £
1 x 2.27m x 0.7m Arch	£7,345	£280 p/w
1 x Switch		
1 x Cable		

MinMoe System Pricing

Item	Purchase £	Rental £
1 x Mini moe	£2,680	£105 p/w
1 x Switch		
1 x Cable		

Extras

Item	Purchase £	Rental £
Laptop	£596	n/a
NVR Recorder	£391	£25p/w
Blackbody Calibrator	£1,210	£45p/w
Installation	-----	£350 -----
Decommission	-----	£175 -----

Extras

Item	Purchase £	Rental £
Laptop	£596	n/a
NVR Recorder	£391	£25p/w
MinMoe Stand	£164	£10p/w
Installation	-----	£350 -----
Decommission	-----	£175 -----

Handheld Thermal Camera



Item

The handheld thermal camera incorporates an integral screen and is designed to allow personnel to accurately detect elevated skin temperature in real time in settings such as office buildings, factories, stations, airports and other public places.

3.5" LCD touch display.

Rechargeable battery.

Battery time: 4-5 hours.

Purchase £

Built-in memory module

Temp range: 30 $^{\circ}\text{C}$ to 45 $^{\circ}\text{C}$

Accuracy: $\pm 0.5^{\circ}\text{C}$

Colour highlight and audio alarm notification.

Supports audio intercom.

160 x 120 thermal resolution.

Live view available on PC, mobile device or external monitor

£3,625
(includes delivery and 30 min online training)

To find out how we can help you

Call: **07825 087 247** or email **byron@debtsquared.com**